

IMPORTANT SAFETY WARNINGS

- Improper or careless use of a firearm and holster may result in serious injury or death. It is the user's responsibility to have thorough knowledge of and be properly trained in all aspects of firearm and holster safety and use.
- Do not carry any handgun with a round in the chamber unless you have received professional training in the use of the handgun and holster and are willing to assume responsibility and risk (including accidental discharge) of carrying a loaded handgun.
- If your handgun is equipped with a safety lever, be sure that safety is engaged when holstering the handgun.
- When drawing a handgun from a holster or placing it into a holster, do not place finger in the trigger guard or near the trigger guard. Position trigger finger adjacent to but away from the trigger and, if possible, support the tip of the finger on the front of the trigger guard.
- When putting a handgun in the holster always place thumb over the hammer or behind the slide.
- Always secure the retaining or safety strap(s) on holster after inserting handgun in holster.
- Never holster any semi-automatic handgun in a single-action mode (except handguns which are single action only; ex. Colt 1911 or the Browning Hi-Power).
- Do not attempt to cock a holstered handgun as this can cause severe damage to the handgun or holster or both and may contribute to an accidental discharge.
- Always place hand on the handgun and holster when running or performing other vigorous activity.
- Do not use customized, modified, worn or broken handguns or those that are not of original manufacturers specifications in Safariland holsters.
- Do not, in any way modify, disassemble or remove any part from this holster.
- Do not rely on any holster being snatch proof. There is no such holster. Rely only on extensive, proper training and vigilance.
- It is the user's responsibility to properly maintain the holster by checking components such as snaps, screw, etc. for proper function.
- Be aware that handguns with lights mounted to them create an opening in the holster that could possibly allow access to the trigger.

WARNING: Failure to heed these warnings or follow the operating instructions may result in accidental discharge of a handgun causing serious injury or death.

EXPRESS LIMITED WARRANTY FOR HOLSTER AND ACCESSORY PRODUCTS

Safariland™ (the "Company") warrants its holster products to be free from defects in materials and workmanship for a period of two (2) years from date of purchase. This warranty is subject to the proper Care and Maintenance of the product and proper use of the product as detailed in the Consumer and Safety Information.

If you believe this product has any defects in materials or workmanship, cease use immediately and contact customer service for a remedy. If a product proves to be defective in material or workmanship, we will repair or replace the product and send it to you at the Company's expense. All returns must include the proof of purchase and documentation specifying the claimed defect.

This is a LIMITED WARRANTY, and is the sole and exclusive warranty of this product by the Company. It shall not be enlarged by any representations, descriptions, course of dealing, trade usage, rendering of technical advice, service or otherwise. Furthermore, it shall not be altered or expanded by any acts, statements, or agreements of any dealer, employee or agent of the Company (other than by a duly authorized officer of the Company).

THE COMPANY MAKES NO OTHER WARRANTIES EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

IN NO EVENT SHALL THE COMPANY BE LIABLE FOR ANY PUNITIVE, EXEMPLARY, OR CONSEQUENTIAL DAMAGES, ANTICIPATED OR LOST PROFITS, INCIDENTAL DAMAGES, LOSS OF TIME, OR OTHER INDIRECT LOSSES OR EXPENSES THAT ARISE FROM ANY CAUSE RELATING TO THE PRODUCT, REGARDLESS OF THE FORM OF THE ACTION, WHETHER IN TORT (INCLUDING NEGLIGENCE), CONTRACT, STRICT LIABILITY OR OTHERWISE, AND REGARDLESS OF WHETHER THE COMPANY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

For any warranty issue, please contact customer care for a prompt resolution to your concern at the number provided below.

(800) 347-1200 or (909) 923-7300.


SAFARILAND™

A BRAND OF THE SAFARILAND GROUP
TOGETHER, WE SAVE LIVES™

3041 FAYE ROAD, JACKSONVILLE, FL 32226
(800)347-1200 (USA ONLY) OR (909) 923-7300 | FAX (909) 923-7400

©2023 SAFARILAND, LLC

USER GUIDE



SAFARILAND™

INNOVATION NOT IMITATION™

MODEL

Incog X



IMPORTANT

READ BEFORE USE

UNDERSTAND ENTIRE GUIDE.
FOLLOW INSTRUCTIONS CAREFULLY.
RETAIN FOR FUTURE REFERENCE.

OVERVIEW

The Incog X is an ergonomic, mission-adaptable, RDS compatible, deep concealment thermoformed IWB holster system. Newly redesigned and now features improved body profile and mounting clip functionality for various IWB carry positions. The holster line has evolved to include either rail-mounted-light compatible or nonlight (gun only) models. The new design is compatible with virtually all red dot sights and the most popular co-witnessing sights. All Incog X gun fits are available for purchase with or without the spare magazine mag caddy option. The completely redesigned mounting clips allow for more adaptability, improved grip acquisition, enhanced concealment and functionality all while reducing complexity and excessive hardware.

QUICK START

Double check that the gun and light model being used are listed on the holster packaging label (Figure 1). If the light being used is equipped with a gun rail and fit optimizing insert feature, be sure that the correct one is installed for the gun model being used when attaching it to the firearm. Insert the gun into the holster. Adjust holster body's red tension screw (Figure 2) to optimize gun fit and retention as desired.



FIG. 1



FIG. 2

If the Incog model purchased includes a mag caddy, insert magazine into it. Adjust mag caddy's red tension screw to customize fit to the desired feel (Figure 3). Attach to Holster Body if preferred or install the extra flat clip provided to use separately if desired (Figure 4).



FIG. 3

Make sure the offset clip's or raised clip's strut Insert is installed and both clips are securely positioned on the holster body (Figure 5). Loosen your belt. Insert the holster inside the waistline of your pants or shorts. Ensure that the belt clips are positioned over-the-belt and that each belt clip's barb seats under the bottom edge of the belt (Figure 6). Retighten your belt to the desired fit and you're ready to go!



FIG. 4



FIG. 5



FIG. 6

HOLSTER

The hybrid holster body design combines a firearm fit optimizing, durable and impact resistant Safarilaminat core with a cooling, easy-to-clean outer microfiber suede skin that simultaneously adds comfort while wicking away moisture. Firearm retention inside the holster is assisted by the integrated passive retention device (PRD). Holstering is easy and the user will feel and hear an audible click when the firearm is properly seated into the holster. Nonlight models feature a PRD design that utilizes the firearm's trigger guard (Figure 7). Light models feature a new PRD design that utilizes the firearm's ejection port geometry (Figure 8). Both light and nonlight Incog X models feature a red washer accented, PRD tension adjustment screw (Figure 2) that can be loosened or tightened to customize fit, feel, and function.



FIG. 7



FIG. 8

MAG CADDY

Each Incog X holster model is available with or without an optional spare magazine mag caddy. Magazine fit inside the mag caddy can be customized by the red washer accented tension screw (Figure 3). Loosen or tighten as needed to optimize fit and feel. The mag caddy can be attached

to the holster body to enhance the IWB holster system or be used and worn independently (Figure 4). To attach mag caddy to the holster body, remove both 1/2" screws, Chicago posts and flat clip (Figure 9). Position the caddy behind the holster body flange with the slots aligned with any pair of upper holster body eyelets. Install the Chicago Posts into the mag caddy slots, from the suede lined backside as shown (Figure 10). Reposition the flat clip and secure the mag caddy to the holster body with the two 5/8" screws provided in the accessory pack. Test fit holster system in the IWB wear position to double check mag caddy ride height and magazine access. If slight positional tweaks are needed to optimize magazine accessibility, loosen the screws and move the mag caddy within the slotted hole range. If larger positional tweaks are needed, remove mag caddy once again and reinstall in a different pair of holster eyelets. To use the mag caddy separately, install the additional flat clip with the two extra 1/4" screws and Chicago posts provided in the accessory kit (Figure 4).



FIG. 9



FIG. 10

BELT CLIPS

All Incog X holster models feature two outboard, durable and rigid polymer, over-the-belt style mounting clips that intuitively open and close into place while IWB positioning. An actuated finger tab flexes to open the clips, allowing for quick holster removal from the belt. The mounting clips will secure onto most belts up to 1-3/4" in width. During IWB use, the holster's interior end is anchored into position with a flat style clip that maximizes concealability and helps secure the mag caddy into position when it's attached (Figure 11). The exterior end of light compatible models features an offset style clip. Nonlight or gun only models incorporate a raised style clip design. Each clip style was carefully designed to complement the different holster model PRD locations while optimizing grip acquisition and offering ride height adjustability. Additional IWB enhancement is presented by the Incog mounting clips' integrated strut feature. The strut specifically enhances concealability for IWB wear by pulling the firearm grip into the body. The strut design includes three different shims sizes 1/8", 1/4" and 3/8" for further concealment customization. The 1/4" strut shim is preinstalled. To swap out shims, depress the locking tab, from the back side of the clip, and slide the tab outwards, away from the holster body (Figure 12).



FIG. 11



FIG. 12